

PIG® Oil-Only Absorbent Boom

BOM304 8" x 10', Absorbs up to 12 gal. per boom, 4 booms

Confine and absorb oil and fuel spills on water.

- Absorbs and retains oils and oil-based liquids - including lubricants and fuels - without taking in a drop of water
- Booms float at surface for easy retrieval, even when saturated
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 400-lb. loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant up to 12 months; meets NFPA 99 standards for static decay
- Strong, zinc-plated carbon steel attachment clips and rings allow you to link booms together for greater length
- Bright white color makes booms easier to see in outdoor environments and clearly shows saturation level
- Can be incinerated after use to reduce waste or for fuels blending



Specifications

| | |
|-------------------------|--|
| Fluid Absorbed | Oils, Fuels, Other Oil-Based Liquids Only |
| Color | White |
| Dimensions | ext. dia. 8" x 10' L |
| Recycled Content | 98% Pre-Consumer Recycled Polypropylene Filler |
| Absorbency | Up to 48 gal. per bag |
| Absorbency per | Up to 12 gal. per boom |
| Brand | PIG |
| Clip/Ring | Zinc Plated Carbon Steel |
| Filler | Polypropylene |
| Skin/Outer Mesh | Skin - Polypropylene, Outer Mesh - Polyester |
| Sold as | 4 booms per bag |
| Weight | 45.5 lbs. |

| | |
|------------------------------------|------------------|
| NSN (National Stock Number) | 7930-01-436-8326 |
| # per Pallet | 8 |
| Application | Spill Response |
| UNSPSC | 47131907 |
| Pigalog® Page Number | <u>Page 65</u> |

Metric Equivalent

| | |
|-----------------------|-------------------------|
| Absorbency per | Up to 45.4 L per boom |
| Absorbency | Up to 181.7 L per bag |
| Dimensions | ext. dia. 20.3cm x 3m L |
| Weight | 20.6 kg |

Technical Information

Certifications, Approvals and Ratings

NFPA 99

Technical Documents

[UV-Resistance Comparison Testing of Spunbond and Meltblown](#)

[Instructions for Using PIG® Absorbent Booms](#)

[PIG® Oil-Only Absorbents](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com