

PIG™ Drive-Over Build-A-Berm® Barrier Straight Section

PLR283 Ideal For Long-Term Custom Containment, High-Traffic Areas, 5.5" x 12' x 2"

Drive-over barrier springs back into shape when heavy vehicles pass. Custom containment berm helps you control liquids in high-traffic areas.

- The Drive-Over Barrier provides semi-permanent containment in high-traffic areas on concrete, asphalt or most sealed surfaces
- Constructed of 40-ounce, vinyl-coated fabric with an open-cell foam core; berm compresses to approximately 1/4" when driven over; springs back to shape when vehicles pass
- Durable enough to withstand indoor or outdoor traffic from trucks, loaded tow motors and other heavy vehicles with sufficient ground clearance
- Secure to floor with sealant and reinforce with predrilled aluminum mounting strips and steel anchors; seal seams with vinyl cement
- Create any configuration by combining with other Build-A-Berm components; ends overlap and can be sealed together for liquid-proof containment
- When used with standard Build-A-Berm Barriers, orange color indicates area where drivers can enter and exit



Specifications

Traffic	Vehicle Traffic
Color	Orange
Dimensions	5.5" W x 12' L x 2" H
Ideal For	Long-Term Custom Containment, High-Traffic Areas
Install/Deploy Type	Glued In Place Barrier
Temperature Limit	Works from -22°F to 160°F
Sold as	1 each
Weight	11.5 lbs.
New Pig Patent	5,820,297
# per Pallet	32
Composition	Cover - 40 oz. Vinyl-Coated Fabric Core - Open-Cell Polyurethane Foam

	Strips - Aluminum
	Anchors - Galvanized Steel

Includes

- 1 - 12" Straight Section Barrier
- 6 - 4' L x 1/8" H x 1" W Mounting Strips
- 33 - 1/4" x 1 5/8" Anchors

UNSPSC	24101907
--------	----------

Pigalog® Page Number

Page 171

Metric Equivalent

Dimensions	14cm W x 3.7m L x 5.1cm H
------------	---------------------------

Weight

5.2 kg

Technical Information

Technical Documents

PIG Build-A-Berm® Barrier

Instructions for PIG Drive-Over Build-A-Berm Barrier

40 CFR 112.7

40 CFR 122.26



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com