

PIG™ Multi-Purpose Epoxy Putty

PTY202 6 - 4 oz. Tubes

Top quality resins bond better and stay stronger so repairs last - we guarantee it! Fix it fast and fix it right with PIG Epoxy Putty.



- Customer-favorite PIG Epoxy Putty sticks to almost anything and cures fast
- Made with the highest-quality epoxy resins to bond better and stay stronger; adheres to steel, glass, masonry and most plastics
- Convenient, premeasured epoxy has Parts A and B in one tube ready for kneading
- Cures concrete-hard in 1 hour for drilling, tapping, sanding or painting
- Nontoxic, VOC- and solvent-free putty can be used on potable water lines
- 3- to 5-minute working time
- A great addition to any toolbox or response kit
- PIG Putty is not intended for making structural repairs



Specifications

Color	Gray
Dimensions	7" L
Handling Time	3 Minutes
Pipe Size	Unlimited
Pipe Pressure	Pressurized, Non-Pressurized
Repair Type	Permanent
Temperature Limit	-20°F (-29°C) to 250°F (121°C) Continuous, 300°F (149°C) Intermittent
Sold as	6 per box
Weight	2.1 lbs.
# per Pallet	300
Composition	15% Epoxy Resins 1.5% Catalyst 83.5% Non-Hazardous Proprietary Ingredient
Application	Multi-Purpose
Shelf Life	2 years
UNSPSC	31201607

Volume 4 oz. Tube

Pigalog® Page Number Page 272

Metric Equivalent

Dimensions 17.8cm L

Weight 1 kg

Technical Information

Certifications, Approvals and Ratings

NSF Certified

CountryNoShip

This product is subject to export restrictions and cannot be shipped to Canada or the European Union.

Certifications, Approvals and Ratings

NSF Certified

CountryNoShip

This product is subject to export restrictions and cannot be shipped to Canada or the European Union.

Technical Documents

[PIG® Repair Putty](#)

[Instructions for PIG Multi-Purpose Epoxy Putty](#)

[PIG® Multi-Purpose Repair Putty](#)

Disclaimers

[For Repair Purposes Only](#)

Not intended for structural applications. For repairing applications only.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com