

Instructions: Portable Golf Car Windshield

Installation

1. First find the top of your Portable Golf Cart Windshield—it is the straight edged side without grommets. Take one of the elastic cords and attach the hook through the top grommet on the right side.
2. Take your Golf Cart Windshield and the hooked cords into your golf cart. Now, working from the inside of your cart, position the top right corner your Golf Cart Windshield (with the hooked cord still attached) against the OUTSIDE front right of the windshield frame of your golf cart. Use your left hand to pull the left side of your Golf Cart Windshield across the front of your golf cart windshield frame and around the left windshield frame to the inside.
Now, with your right hand, CAREFULLY take the left end of the hooked cord and attach it to the opposite grommet on the left hand side.
3. Carefully attach the other two elastic cords in the same way. When you are done you will have three cords stretching across the inside of your windshield; one across the top, one across the middle and one across the bottom.



4. Adjust as necessary to get a nice fit.

Storage

DO NOT STORE YOUR COVER FOR LONG PERIODS WHEN WET—your cover could mildew.

Cleaning

Your Golf Cart Windshield can be cleaned with warm water and a SOFT cloth. DO NOT USE SOAP OR ANYTHING ABRASIVE WHEN CLEANING THE CLEAR VINYL—cleansers may scratch the clear vinyl.

Warranty

Your Classic Portable Golf Cart Windshield is factory warranted for workmanship and materials for one year after purchase.

This warranty assumes normal use and conditions. Trailering your golf cart with this windshield on it will invalidate this warranty.

- Three provided hooked elastic cords secure your Portable Golf Cart Windshield to your golf cart.



Classic Accessories, Inc.
Kent, WA, USA 98032
www.classicaccessories.com

©2007