


Universe	Professional
Type	Verticality
Category	Ropes
Subcategory	Low stretch kernmantel ropes




AXIS 11 mm (length in feet)


The AXIS 11 mm low stretch kernmantel rope is designed for work at height. The standard diameter ensures a good grip for easier handling. The EverFlex technology guarantees great flexibility and consistent performance over time. Rope available in six colors and four lengths.



The standard rope diameter ensures a good grip for easier handling.



EverFlex technology ensures great flexibility over time and under any conditions (water, dust, mud...), allowing it to maintain consistent handling and optimal performance with devices.



It is possible to order a rope of a specified length.



The addition of sewn terminations manufactured on one or both ends provides a ready-to-use rope. These terminations have a protective sheath that keeps the connector in position and facilitates handling.

Short Description Low stretch kernmantel rope with good handling for work at height

Selling Points

- Standard diameter ensures a good grip for easier handling
- Consistent performance over time:
 - construction with nylon core and polyester sheath, with specific weave
 - EverFlex technology ensures great flexibility over time and under any conditions (water, dust, mud...), allowing it to maintain excellent handling and optimal performance with devices
- Available in six colors: white, yellow, black, blue, red and orange
- Standard lengths: 150, 200, 600 and 1200 ft
- Customization on request:
 - option of ordering a rope of a specified length (up to 1800 ft)
 - addition of sewn terminations manufactured on one or both ends, providing a ready-to-use rope. These terminations have a protective sheath that keeps the connector in position and facilitates handling. They are also stronger than a figure-eight knot

Specification

- Diameter: 11mm
- Material(s): polyester, nylon
- Certification(s): CE EN 1891 type A, EAC, NFPA 1983 Technical Use
- Weight per meter: 82g
- Strength tied with figure-eight knot: 19kN
- Strength with sewn termination: 22kN
- Impact force (factor 0,3): 5,2kN
- Number of factor 1 falls: 12
- Construction: 32 carrier
- Percentage of sheath: 41%
- Static elongation: 3%

Specifications by reference

Reference(s)	R074AA00	R074AA01	R074AA02	R074AA35
				
Length	150 ft	150 ft	150 ft	150 ft
Color(s)	white	yellow	black	blue
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	2	2	2	2
EAN	3342540816060	3342540816077	3342540816084	3342540822825

Reference(s)	R074AA36	R074AA37	R074AA06	R074AA07
				
Length	150 ft	150 ft	200 ft	200 ft
Color(s)	red	orange	white	yellow
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	2	2	1	1
EAN	3342540822832	3342540822849	3342540816121	3342540816138

Reference(s)	R074AA08	R074AA41	R074AA42	R074AA43
				
Length	200 ft	200 ft	200 ft	200 ft
Color(s)	black	blue	red	orange
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540816145	3342540822887	3342540822894	3342540822900

Reference(s)	R074AA15	R074AA16	R074AA17	R074AA18
				
Length	600 ft	600 ft	600 ft	600 ft
Color(s)	white	yellow	black	blue
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540816213	3342540816220	3342540816237	3342540816244

Reference(s)	R074AA19	R074AA20	R074AA27
			
Length	600 ft	600 ft	1200 ft

Color(s)	red	orange	white
Made in	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years
Inner Pack Count	1	1	1
Quantity Per Box	1	1	1
EAN	3342540816251	3342540816268	3342540816336

Accessory(ies) PROTEC
SET CATERPILLAR
ROLL MODULE

Related product(s) I'D® EVAC
I'D® S
ASAP® LOCK