

Instructions: 5th Wheel Cover

⚠️WARNING!

Installation is best done with two people. **Never install on a windy day or when your 5th wheel roof is slippery. Please take care whenever you are on a ladder or the roof.**

CAUTION

Please consult your RV owners manual.

Tools Needed:

Scissors

Matches or lighter (optional)

Screwdriver (usually Phillips head) for roof antennas

Installation

1. Cover or tape any sharp edges on your 5th wheel that could wear against your cover. Be sure to lower any roof antennas.

2. Unroll the cover next to your 5th wheel with the Classic logo on your cover at the front of your 5th wheel and facing the outside. Unzip the side and rear panels.

3. On larger 5th wheels it's easiest to install your cover from the roof. Carefully climb up on the roof pulling the cover front with you. Lower the front of your cover down over the front of your 5th wheel then carefully move toward the back pulling the cover and letting it fall down the sides of your 5th wheel. Climb down the rear ladder and locate the ladder cap. (The cap helps keep the top of the ladder from stressing the cover). Fit it over the ladder top and attach it to the rungs with the hook and loop straps. Now pull the back end of the cover down the back of the 5th wheel.

4. Zip all the panels closed on your cover and then pull the elasticized corners down over both bumpers of your 5th wheel.

5. Locate the hook and loop straps on the upper part of the flaps that fold in under the nose of your 5th wheel. Adjust them to fit your cover to the exact length of the nose of your 5th wheel.

6. Once the length of the nose of the cover is correctly adjusted, locate one of the supplied ropes and the D-rings sewn in along the flaps that fold in under the nose of your 5th wheel. Tighten the rope and tie it off onto the D-rings located opposite each other. Repeat with the lower D-ring.

7. Tie an end of the supplied rope onto one of the D-rings along the bottom hem. Put a small rock in the provided toss bag, close the top and tie the free end of the rope to the bag D-ring. Now toss the bag and rope under your 5th wheel to the D-ring on the opposite side. Take the rope off the bag and, allowing enough to make a knot, cut it off and tie it to the D-ring. Repeat with the other D-rings. To keep the rope ends from fraying you can carefully melt the ends with a match or lighter.

8. Adjust the strap length on the white tension panels across the front and back to fit your 5th wheel. Don't over tighten—the straps should be snug, not drum tight. To attach the straps into the side-release buckles just insert the clip into the buckle. To release the buckle press the buttons on both sides and pull the clip out of the buckle.

Use and Storage

Your cover can be unzipped for access to the passenger side and rear. The panels can be rolled up and held in place with the hook and loop straps toward the top of each panel. A handy storage bag is provided. To fit it in the bag fold your cover and roll



the cover tightly rather than stuffing it. Never store a wet cover in the storage bag or confined area as the cover can be damaged by mildew.

Care

Spot clean with water, a mild soap and a sponge. Don't use abrasive cleaners or brushes.

Three Year Limited Warranty

If this cover fails due to a defect in workmanship and materials within three years from the date of purchase Classic Accessories will repair or replace it free of charge.

Trailering or towing your 5th wheel with your cover on will invalidate the warranty.

This warranty gives you specific rights and you may also have other rights which vary from state to state.



Classic Accessories, Inc.
Kent, WA, USA 98032
www.classicaccessories.com