



LF SERIES

High velocity ceiling or wall mount fans suitable for wet locations

FEATURES

- Ceiling or wall mount high velocity fan.
- 18" blade diameter.
- Commercial duty 3 speed motor with pull chain control.
- All metal construction.
- 1/8 hp motor.
- Epoxy coated OSHA guard.
- 9ft heavy duty 120V cord with cord wrap.
- Steel wall (ceiling) mount assembly.

PERFORMANCE SPECIFICATIONS

MODEL	SIZE	HP	VOLTS	AMPS	Phs	RPM	SPEED	CFM	CMF / W	WEIGHT (LBS)
LF18HVW	18"	1/8	120	1.41/1.22/1.01	1	1449/1273/1024	3	5043/4394/3540	30.9 / 30.4 / 29.1	26



HAF-ZO

HAF SERIES

Horizontal airflow fans

FEATURES

- Available in 14", 16", 18", 20" and 24" sizes.
- Fans available with bright zinc plated or white polyolefin OSHA guard depending on size.
- Totally enclosed motors.
- 120V grounded cord and plug
- Most models available in White as an alternate as a special order. Call factory for details.



HAF18-W

HAF18-W FEATURES

- 18" horizontal air flow fan.
- Totally enclosed motor.
- Powder coated guard has wide spacing to eliminate the build up of debris.
- 115V, 8 foot grounded cord & plug.

PERFORMANCE SPECIFICATIONS

MODEL	DESCRIPTION	VOLT	MOTOR HP	WATT	AMPS	CFM	CFM / WATT	RPM	SPEED	SPEED CONTROL
HAF14-ZO*	14" Zinc dipped with Hanging Bracket	120V	1/16	60	0.6	1620	-	1550	Variable	Optional
HAF18-W	18" powder coated with Hanging Bracket	120V	1/8	113	1.0	4227	35.8	1648	Variable	Optional
HAF18-PO	18" White Polyolefin with OSHA Guard with Strap Mount	120V	1/8	113	1.0	4227	35.8	1648	Variable	Optional
HAF20-ZO*	20" Zinc dipped with Hanging Bracket	120V	1/8	119	1.0	4997	40.9	1621	Variable	Optional
HAF24-ZO*	24" Zinc dipped with Hanging Bracket	120V	1/4	193	1.7	7951	40.2	1138	Variable	Optional

*Special order. Call for availability.