

Head / Blade Type	Part Number	Trimmer Line Diameters		FSA 30	FSA 57*	FSA 60 R	FSE 60*	FSA 80 R*	FSA 80	FSA 86 R	FSA 120 R*	FSA 120	FSA 135 FSA 135 R	FSA 200 FSA 200 R	FS 38* FS 40 C-E* FS 50 C-E*	FS 56 C-E	FS 56 RC-E FS 70 R FS 94 R	FS 91 R FS 111 R FS 131 R	FS 111 RX	FS 91 FS 111 FS 131	FS 240 FS 251	FS 240 R FS 251 R	FS 311	FS 361 C-EM FS 461 C-EM	FS 561 C-EM	FSB-KM with KM 56 RC-E KM 91 R / KM 111 R	FS-KM with KM 56 RC-E	FS-KM with KM 91 R / KM 94 R KM 111 R / KM 131 R	FS-KM with KMA 80 R / KMA 120 R / KMA 135 R				
		Standard	Optional																														
LIGHT GRASS TRIMMER HEADS																																	
AutoCut® 2-2	4008 710 2103	.080"	—		● ³																												
AutoCut® C 3-2	4009 710 2106	.080"	—	●	● ⁴																												
AutoCut® C 4-2	4006 710 2123	.080"	—																														
AutoCut® 5-2	4006 710 2103	.080"	—				●								●																		
AutoCut® C 6-2 .080"	4006 710 2126	.080"	.095"				●								●																		
AutoCut® C 6-2 .095"	4006 710 2140	.095"	.080"			●	●			●					●																		
AutoCut® C 26-2	4006 710 2169	.095"	.105"					●	●		●	●	●	●		●	●	●	●	●	●	●	●						●	●	●	●	
AutoCut® 27-2	4002 820 2302	.095"	.105"					●	●		●	●	●	●		●	●	●	●	●	●	●							●	●	●	●	
AutoCut® 36-2	4002 710 2170	.105"	.118"/.130"										●					●	●	●	●	●											
AutoCut® 46-2	4003 710 2115	.105"	.118"/.130"																				●	●									
AutoCut® 56-2	4005 710 2107	.105"	.118"/.130"																							●							
DuroCut 5-2	4006 710 2131	.080"	.065"/.095"			●				●					●																		
DuroCut 20-2	4002 710 2182	.120"	.080"/.095"/.105"				●	●	●		●	●	●	●		●	●	●	●	●	●	●								●	●	●	●
DuroCut 40-4	4005 710 2114	.155"	.120"/.130"																				●	●	●								
FixCut™ 31-2	4001 710 2105	—	.080"/.095"/.105"																			● ²	● ²							●	●	●	
STIHL SuperCut™ 20-2	4002 710 2184	.095"	—										●																				
STIHL SuperCut™ 40-2	4003 710 2142	.095"	—																														
TrimCut™ C 32-2	4002 710 2198	.095"	.105"/.118"					●	●		●	●	●			●	● ¹	●	●	●	●	●											
TrimCut™ C 42-2	4003 710 2122	.105"	.095"/.118"																				●	●									
TrimCut™ C 52-2	4005 710 2117	.105"	.095"/.118"/.130"																							●							



- * Trimmers equipped with loop handles.
- Approved for use with designated unit as originally equipped.
- Approved for use with loop handle (R) only if equipped with barrier bar deflector kit and a single or double shoulder harness.
- Approved for use with bike handle, double harness and limit stop.
- ¹ Not for use on FS 94 R
- ² Not for use on FS 240 or FS 240 R
- ³ Only fits FSA 57 trimmers starting with serial number 9XXXXXXX.
- ⁴ Only fits FSA 57 trimmers starting with serial number 5XXXXXXX.

Note: Numbers with "mm" show arbor size. Consult your instruction manual or your authorized STIHL Dealer for approved cutting head/deflector combinations.

Note: Barrier bar and large deflector must be attached when using a metal blade with loop-handle (R) trimmer.

Note: Specifications are as of Oct. 1, 2023. For most recent updates, visit STIHLusa.com.

IMPORTANT INFORMATION
WARNING: Improper use of any brushcutter trimmer can cause serious or fatal injury. Read, understand and follow all safety instructions in your instruction manual. To reduce the risk of injury from blade contact, circular saw blades may be used on FS brushcutters that have a bicycle handle and double shoulder harness and not on FS brushcutters with a "J" handle or loop handle (R). Other rigid blades may be used on FS brushcutters having a bicycle handle, a "J" handle, or a loop handle equipped with a barrier bar. To reduce the risk of eye injury, always wear proper eye protection. Always use the appropriate deflector for the type of cutting attachment, as explained in your instruction manual.

