



DRIVING SURFACE PERFECTION

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet RPEWGAL-US-SDS

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 09/02/2020

Revision date: 11/27/2020

Supersedes: 09/02/2020

Version: 1.1

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Trade name : RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL  
 Product code : UP4847  
 UP Number : UP4847

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Coatings and paints, thinners, paint removers  
 Recommended use : Topcoat

#### 1.3. Supplier

U-POL US Inc  
 108 Commerce Way  
 Easton, PA 18040 - United States  
 T 1-800-340-7824 - F 1-800-787-5150  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture


##### GHS US classification

Flammable aerosol Category 1	Extremely flammable aerosol
Gases under pressure Liquefied gas	Contains gas under pressure; may explode if heated
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Carcinogenicity Category 2	Suspected of causing cancer
Specific target organ toxicity — Single exposure, Category 3, Narcosis	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 2	May cause damage to organs through prolonged or repeated exposure

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Extremely flammable aerosol  
 Contains gas under pressure; may explode if heated  
 Causes serious eye irritation  
 May cause drowsiness or dizziness  
 Suspected of causing cancer  
 May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

If medical advice is needed, have product container or label at hand.  
 Keep out of reach of children.  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Do not breathe vapors, spray, fume.  
 Wash hands thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear eye protection, protective gloves, protective clothing.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If exposed or concerned: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
methyl acetate	(CAS-No.) 79-20-9	23 – 43	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
titanium(IV) oxide	(CAS-No.) 13463-67-7	5 – 23	Carc. 2, H351
reaction mass of ethylbenzene, m-xylene and p-xylene		< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
hydrocarbons, C9, aromatics	(CAS-No.) 64742-95-6	< 5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
cyclohexanone	(CAS-No.) 108-94-1	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after eye contact : Eye irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.  
Reactivity : Extremely flammable aerosol.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapors, spray, fume. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapors, fume, spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

titanium(IV) oxide (13463-67-7)		
ACGIH	Local name	Titanium dioxide
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
cyclohexanone (108-94-1)		
ACGIH	Local name	Cyclohexanone
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	50 ppm

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>cyclohexanone (108-94-1)</b>		
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>methyl acetate (79-20-9)</b>		
ACGIH	Local name	Methyl acetate
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	610 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>		
Not applicable		
<b>hydrocarbons, C9, aromatics (64742-95-6)</b>		
Not applicable		

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Aerosol.  
: white

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Fruity odour Mild odour Ether-like odour Odourless Almost odourless Aromatic odour Pleasant odour Petroleum-like odour Sweet odour Peppermint odour Acetone odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -60 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.782 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

As Packaged Regulatory VOC	: 668 g/l (5.6 lbs/gal)
As Packaged Actual VOC	: 516 g/l (4.3 lbs/gal)
As Applied Regulatory VOC	: 668 g/l (5.6 lbs/gal)
As Applied Actual VOC	: 516 g/l (4.3 lbs/gal)
Water Content	0 wt%
Volatiles	: 85.6 wt%
% HAPS	: 0.1 wt%
Percent Solids	: 14.4 wt%
Percent Solids	: 5.74 vol %

Maximum Incremental Activity (MIR)	: 0.73
MIR EPA Aerosol Category	: ABT 1.75 - Automotive Bumper and Trim Product
MIR CARB Aerosol Category	: ABT 1.70 - Automotive Bumper and Trim Product - Specialty Coatings (B)

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

<b>titanium(IV) oxide (13463-67-7)</b>	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))

<b>cyclohexanone (108-94-1)</b>	
LD50 oral rat	1890 mg/kg body weight (BASF test, Rat, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	1100 mg/kg (BRENNTAG test)
LC50 Inhalation - Rat	> 6.2 mg/l air Animal: rat
ATE US (oral)	1890 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

<b>methyl acetate (79-20-9)</b>	
LD50 oral rat	6482 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	49 mg/l
ATE US (oral)	6482 mg/kg body weight
ATE US (vapors)	49 mg/l/4h
ATE US (dust, mist)	49 mg/l/4h

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
LD50 oral rat	3523 mg/kg (EU Method B.1 (Acute Toxicity (Oral)), rat, male)
LD50 dermal rabbit	12126 mg/kg body weight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6350 ppm/4h (4 h, EU Method B.2 (Acute Toxicity (Inhalation)), rat, male, Inhalation, vapours)
ATE US (oral)	3523 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	6350 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

<b>hydrocarbons, C9, aromatics (64742-95-6)</b>	
LD50 oral rat	8400 ml/kg
LD50 dermal rabbit	3160 mg/kg body weight (OECD Guideline 402 (Acute Dermal Toxicity), rat, male/female)
LC50 Inhalation - Rat [ppm]	3400 ppm/4h

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Suspected of causing cancer.

<b>titanium(IV) oxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>cyclohexanone (108-94-1)</b>	
IARC group	3 - Not classifiable

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified  
STOT-single exposure : May cause drowsiness or dizziness.

<b>methyl acetate (79-20-9)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
STOT-single exposure	May cause respiratory irritation.

<b>hydrocarbons, C9, aromatics (64742-95-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

<b>cyclohexanone (108-94-1)</b>	
NOAEL (oral, rat, 90 days)	143 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

<b>methyl acetate (79-20-9)</b>	
LOAEC (inhalation, rat, vapor, 90 days)	2000 mg/l
NOAEC (inhalation, rat, vapor, 90 days)	1057 mg/m <sup>3</sup>

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day ( OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), female)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

<b>hydrocarbons, C9, aromatics (64742-95-6)</b>	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight/day
NOAEC (inhalation, rat, vapor, 90 days)	900 – 1800 mg/m <sup>3</sup>

Aspiration hazard : Not classified  
Viscosity, kinematic : No data available  
Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after eye contact : Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>titanium(IV) oxide (13463-67-7)</b>	
LC50 fish 1	155 mg/l Test organisms (species): other: Japanese Medaka
EC50 Daphnia 1	19.3 mg/l Test organisms (species): Daphnia magna
EC50 Daphnia 2	27.8 mg/l Test organisms (species): Daphnia magna
ErC50 (algae)	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

<b>cyclohexanone (108-94-1)</b>	
LC50 fish 1	527 – 732 mg/l Test organisms (species): Pimephales promelas
EC50 Daphnia 1	> 100 mg/l Test organisms (species): Daphnia magna
ErC50 (algae)	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Read-across, GLP)

<b>methyl acetate (79-20-9)</b>	
LC50 fish 1	250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 Daphnia 1	1026.7 mg/l Test organisms (species): Daphnia magna

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>reaction mass of ethylbenzene, m-xylene and p-xylene</b>	
LC50 fish 1	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 Daphnia 1	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

<b>hydrocarbons, C9, aromatics (64742-95-6)</b>	
LC50 fish 1	9.22 mg/l (Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l 48 h, Daphnia magna
ErC50 (algae)	2.9 mg/l

### 12.2. Persistence and degradability

<b>titanium(IV) oxide (13463-67-7)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

<b>cyclohexanone (108-94-1)</b>	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.232 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.605 g O <sub>2</sub> /g substance
ThOD	2.605 g O <sub>2</sub> /g substance

<b>methyl acetate (79-20-9)</b>	
Persistence and degradability	Readily biodegradable in water.

<b>hydrocarbons, C9, aromatics (64742-95-6)</b>	
Persistence and degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>titanium(IV) oxide (13463-67-7)</b>	
Bioaccumulative potential	Not bioaccumulative.

<b>cyclohexanone (108-94-1)</b>	
BCF other aquatic organisms 1	2.4 (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>methyl acetate (79-20-9)</b>	
BCF fish 1	< 1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

<b>titanium(IV) oxide (13463-67-7)</b>	
Ecology - soil	Low potential for mobility in soil.

<b>cyclohexanone (108-94-1)</b>	
Surface tension	0.034 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)
Ecology - soil	Highly mobile in soil.

<b>methyl acetate (79-20-9)</b>	
Surface tension	24 mN/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols (flammable), 2.1  
UN-No.(DOT) : UN1950  
Proper Shipping Name (DOT) : Aerosols  
flammable  
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115  
Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None  
DOT Packaging Bulk (49 CFR 173.xxx) : None  
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials  
Emergency Response Guide (ERG) Number : 126  
Other information : No supplementary information available.

### Transportation of Dangerous Goods

Transport document description : UN1950 AEROSOLS (flammable), 2.1  
UN-No. (TDG) : UN1950  
Proper Shipping Name (Transportation of Dangerous Goods) : AEROSOLS  
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas  
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.  
(2) Subsection (1) does not apply to self-defence spray.  
Explosive Limit and Limited Quantity Index : 1 L

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Passenger Carrying Road Vehicle or Passenger : 75 L  
Carrying Railway Vehicle Index

### Transport by sea

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1  
UN-No. (IMDG) : 1950  
Proper Shipping Name (IMDG) : AEROSOLS  
Class (IMDG) : 2 - Gases

### Air transport

Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1  
UN-No. (IATA) : 1950  
Proper Shipping Name (IATA) : Aerosols, flammable  
Class (IATA) : 2

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### titanium(IV) oxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### cyclohexanone (108-94-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ : 5000 lb

#### methyl acetate (79-20-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### reaction mass of ethylbenzene, m-xylene and p-xylene

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### hydrocarbons, C9, aromatics (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### titanium(IV) oxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

#### cyclohexanone (108-94-1)

Listed on the Canadian DSL (Domestic Substances List)

#### methyl acetate (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

#### reaction mass of ethylbenzene, m-xylene and p-xylene

Listed on the Canadian DSL (Domestic Substances List)

#### hydrocarbons, C9, aromatics (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

#### titanium(IV) oxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

# RAPTOR 1K PRO ENAMEL WHITE GLOSS AEROSOL

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**⚠ WARNING:** This product can expose you to ethylbenzene, which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).


Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
toluene(108-88-3)		X				7000 µg/day
ethylbenzene(100-41-4)	X				54 µg/day (inhalation); 41 µg/day (oral)	

Component	State or local regulations
titanium(IV) oxide(13463-67-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
cyclohexanone(108-94-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
methyl acetate(79-20-9)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Revision date : 11/27/2020
- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
- NFPA reactivity : 3 - Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction but that require a strong initiating source or must be heated under confinement before initiation.



SDS US GHS (GHS HazCom2012)

*For professional use only.*

*The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).*