

SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Ultra1Plus™ UltraVision Windshield Washer De-Icer -32F

1.1 Product Identifier:

Product form: Mixture

Product name: UltraVision Windshield Washer Fluid De-Icer -32F

Product code: U1PWWFDI

1.2. Use of the substance/mixture: Windshield washer fluid

1.3. Company Identification (Details of the supplier of the safety data sheet):

Ultrachem LLC

1444 Northwest 82 Ave.

Doral, FL. 33126 USA

Phone +1 (786) 953 - 6132

www.ultra1plus.com

U1Dynamics Manufacturing LLC

4468 Genoa-Red Bluff Rd.

Houston, TX. 77059 USA

Phone +1 (786) 953 - 6132

1.4. Transportation Emergency Response

CHEMTREC: (800) 424-9300 or (703) 527-3887

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture:

GHS-US classification:

Flammable liquids, Category 3	H226	Flammable liquid and vapor
Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Acute toxicity (dermal), Category 3	H311	Toxic in contact with skin.
Acute toxicity (inhalation:dust,mist)	H332	Harmful if inhaled.
Specific target organ toxicity — single exposure, Category 1	H370	Causes damage to organs (May cause blindness if swallowed)
Full text of H statements: see section 16		

2.2. Label elements:

GHS-US labelling:

Hazard statements (GHS-US):



GHS02



GHS06



GHS08

Signal word (GHS-US): Danger

Precautionary statements (GHS-US):

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. heat, hot surfaces, open flames, and sparks.

Keep container tightly closed.

Ground/Bond container and receiving equipment

Use explosion-proof electrical, lighting, ventilating equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist, spray, and vapors.

Wash affected areas thoroughly after handling.

Do not eat, drink, or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear personal protective equipment as required.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If exposed: Call a poison center/doctor.

If swallowed: Immediately call doctor/physician or poison center. Rinse Mouth

Call doctor/physician or poison center if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

In case of fire: Use Carbon dioxide, Dry powder, foam, sand to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations

2.3. Other hazards: No additional information available

2.4. Unknown acute toxicity (GHS US): No data available

SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances: Not applicable

3.2 Mixtures:

Name	Product identifier	% by wt	GHS-US classification
water	(CAS-No.) 7732-18-5	>= 67	Not classified
methanol	(CAS-No.) 67-56-1	<= 33	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of hazard classes and H-statements: see section 16

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures:

First-aid measures general: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation: Ensure fresh air breathing. Allow the victim to rest.

- First-aid measures after eye contact: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. Take victim to an ophthalmologist if irritation persists.
- First-aid measures after skin contact: Take off immediately all contaminated clothing. Rinse immediately with plenty of water (for at least 15 minutes). If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
- First-aid measures after ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed:

- Symptoms/effects after inhalation: High concentrations may cause central nervous system characterized by severe headaches, dizziness, nausea, and confusion. May cause irritation of the nose and throat.
- Symptoms/effects after skin contact: Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking, and redness.
- Symptoms/effects after eye contact: May cause severe irritation.
- Symptoms/effects after ingestion: May cause nausea, abdominal pain, headache, shortness of breath, visual impairment, and blindness. Severe poisoning can lead to coma and death.
- Chronic symptoms: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin, Dry skin, Skin rash/inflammation, Headache, Feeling of weakness, Disturbed tactile sensibility, visual disturbances, Sleeplessness, Gastrointestinal complaints, Cardiac and blood circulation effects.

4.3. Indication of any immediate medical attention and special treatment needed: Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances, and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. This product contains/consists of methanol which can cause intoxication and depression of the central nervous system.

SECTION 5 FIRE FIGHTING MEASURES

5.1. Extinguishing media:

- Suitable extinguishing media: ABC powder. Foam. Dry powder. Carbon dioxide. Sand.
- Unsuitable extinguishing media: Do not use a heavy water stream. May spread fire.

5.2. Special hazards arising from the substance or mixture:

- Fire hazard: Flammable liquid and vapor. Vapors are heavier than air and may travel along the ground or may be moved by ventilation.

Explosion hazard: Heat may build pressure, rupturing closed containers, spreading fire, and increasing risk of burns and injuries.

5.3. Special protective equipment and precautions for fire-fighters:

Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent firefighting water from entering the environment.

Protection during firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment, and emergency procedures

General measures: Do not breathe mist, spray, vapors. In case of inadequate ventilation wear respiratory protection. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel:

Emergency procedures: Evacuate unnecessary personnel. Keep upwind. Mark the danger area.

6.1.2. For emergency responders:

Protective equipment: Equip cleanup crew with proper protection.

Emergency procedures: Ventilate area.

6.2. Environmental precautions: Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up:

For containment: Contain released product, pump into suitable containers. Dam up the liquid spill. Plug the leak, cut off the supply. Try to reduce evaporation. Take account of toxic/corrosive precipitation water. Dilute combustible/toxic gases/vapors with water spray.

Methods for cleaning up: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections: For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling:

Additional hazards when processed: In use, may form flammable vapor-air mixture.

Precautions for safe handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

Hygiene measures: Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities:

Technical measures: Use explosion-proof ventilating, lighting, electrical equipment. Ground/bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed.

Storage conditions: Keep only in the original container in a cool, well-ventilated place away from: Direct sunlight.
Keep container closed when not in use.

Incompatible products: Strong bases. Strong acids.

Incompatible materials: Sources of ignition.

7.3. Specific end use(s): No additional information available

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters:

methanol (67-56-1)		
ACGIH	Local name	Methanol
ACGIH	ACGIH TWA (ppm)	200 ppm (Skin)
ACGIH	ACGIH ACGIH STEL (ppm)	250 ppm (Skin)
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³ (Skin)
OSHA	OSHA PEL (TWA) (ppm)	200 ppm (Skin)
water (7732-18-5)		
Not applicable		

8.2. Appropriate engineering controls: No additional information available.

8.3. Individual protection measures/Personal protective equipment:

Personal protective equipment: Avoid all unnecessary exposure. Gloves. Safety glasses.

Hand protection: Wear protective gloves.

Eye protection: Chemical goggles or safety glasses.

Respiratory protection: In case of inadequate ventilation wear respiratory protection. Wear an appropriate mask.

Skin and body protection: Wear suitable protective clothing.



Other information: Do not eat, drink, or smoke during use.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Physical state:	liquid
Color:	blue
Odor:	alcohol
Odor threshold:	No data available
Relative evaporation rate (butylacetate=1):	Greater than n-butyl acetate
Freezing point:	-28.9 °C (-20 °F)
Boiling point:	81.7 °C (179 °F)
Flash point:	33.3 °C (92 °F)
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Flammability (solid, gas):	No data available
Vapor pressure:	43 mm Hg @ 20 °C
Relative vapor density at 20 °C:	Heavier than air
Specific Gravity:	0.96 @ 20 °C
Solubility:	Water: Complete
Log Pow:	No data available
Log Know:	No data available
Viscosity, kinematic:	No data available
Viscosity, dynamic:	No data available
Explosive limits:	6 - 36 vol %
Explosive properties:	No data available
Oxidizing properties:	No data available

9.2 Other information:

VOC content: <33 %

SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity: No additional information available

10.2. Chemical stability: Stable.

10.3. Possibility of hazardous reactions: Hazardous polymerization will not occur.

10.4. Conditions to avoid: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials: Keep away from strong acids, strong bases, and oxidizing agents.

10.6. Hazardous decomposition products: Fume. Carbon monoxide. Carbon dioxide.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity: Not classified

methanol (67-56-1)	
LD50 oral rat	1187 - 2769 mg/kg bodyweight (BASF test, Rat, Male / female, Weight of evidence, Aqueous solution, Oral, 7 day(s))
LD50 dermal rabbit	17100 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)
LC50 inhalation rat (mg/l)	128.2 mg/l/4h (BASF test, 4 h, Rat, Male/female, Weight of evidence)
ATE US (oral)	100 mg/kg bodyweight
ATE US (dermal)	300 mg/kg bodyweight
ATE US (gases)	700 ppmv/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust,mist)	0.5 mg/l/4h

Skin corrosion/irritation: Not classified

pH: 7

Serious eye damage/irritation: Not classified

pH: 7

Respiratory or skin sensitization: Not classified

Germ cell mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive toxicity: Not classified

STOT-single exposure: Causes damage to organs (May cause blindness if swallowed).

STOT-repeated exposure: Not classified

Aspiration hazard: Not classified

Symptoms/effects after inhalation: High concentrations may cause central nervous system characterized by severe headaches, dizziness, nausea and confusion. May cause irritation of the nose and throat.

Symptoms/effects after skin contact: Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking, and redness.

Symptoms/effects after eye contact: May cause severe irritation.

Symptoms/effects after ingestion: May cause nausea, abdominal pain, headache, shortness of breath, visual impairment, and blindness. Severe poisoning can lead to coma and death.

Chronic symptoms: ON CONTINUOUS/REPEATED

EXPOSURE/CONTACT: Red skin, Dry skin, Skin rash/inflammation, Headache, Feeling of weakness, Disturbed tactile sensibility, Visual disturbances, Sleeplessness, Gastrointestinal complaints, Cardiac and blood circulation effects.

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity:

methanol (67-56-1)	
LC50 fish 1	15,400.00 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	18,260.00 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	22,000.00 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability:

methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.50 g O ₂ /g substance

12.3. Bioaccumulative potential:

methanol (67-56-1)	
BCF fish 1	1 - 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Log Pow	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil:

methanol (67-56-1)	
Surface tension	0.02 N/m (20 °C)
Log Koc	0.09 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects:

Effect on the ozone layer: No known effect on the ozone layer.
 Other information: Avoid release to the environment.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods:

Product/Packaging disposal recommendations: Dispose in a safe manner in accordance with local/national regulations.
 Ecology - waste materials: Avoid release to the environment.

SECTION 14 TRANSPORT INFORMATION

14.1 Department of Transportation (DOT): In accordance with DOT

Non-Bulk: In inner packaging no more than 5.0 L (1.3 Gallons): Proper Shipping Name: Limited Quantity of Class III Per 49 CFR Part 173.150 (PG III, inner packaging no more than 5.0L)

Bulk (in quantities larger than 5.0L [1.3 gallons] in a single container).

Transport document description:	UN1993 Flammable liquids, n.o.s., 3, III
UN-No. (DOT):	UN1993
Proper Shipping Name (DOT):	Flammable liquids, n.o.s.
Class (DOT):	3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT):	III - Minor Danger
Hazard labels (DOT)	3 - Flammable liquid



DOT Packaging Non-Bulk (49 CFR 173.xxx):	203
DOT Packaging Bulk (49 CFR 173.xxx):	242
DOT Symbols:	G - Identifies PSN requiring a technical name
DOT Packaging Exceptions (49 CFR 173.xxx):	150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27):	60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75):	220 L
DOT Vessel Stowage Location:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number:	128
Other information:	No supplementary information available.

14.2 Transportation of Dangerous Goods:

Refer to current TDG Canada for further Canadian regulations.

14.3 Transport by sea: In accordance with IMDG / IMO

Transport document description (IMDG):	UN 1992 Flammable Liquid, Toxic, n.o.s. (methanol), 3, III
UN-No. (IMDG):	1992
Proper Shipping Name (IMDG):	Flammable Liquid, Toxic, n.o.s. (methanol)
Class (IMDG):	3 - Flammable liquids
Packing group (IMDG):	III - substances presenting low danger

14.4 Air transport: In accordance with IATA / ICAO

Transport document description (IATA): UN 1992 Flammable Liquid, Toxic, n.o.s.
(methanol), 3 (6.1), III
UN-No. (IATA): 1992
Proper Shipping Name (IATA): Flammable Liquid, Toxic, n.o.s. (methanol)
Class (IATA): 3 - Flammable Liquids
Packing group (IATA): III - Minor Danger
Subsidiary risks (IATA): 6.1 - Toxic substances

SECTION 15 REGULATORY INFORMATION

15.1. US Federal regulations

UltraVision Windshield Washer Fluid De-Icer -32F	
EPA TSCA Regulatory Flag:	Toxic Substances Control Act (TSCA): The intentional ingredients of this products are listed.
SARA Section 302 Threshold Planning Quantity (TPQ):	None
SARA Section 311/312 Hazard Classes:	Delayed (chronic) health hazard. Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting:	33 % (Methanol CAS # 67-56-1)

methanol (67-56-1)	
CERCLA RQ	5000 lb(s) (2270 kg)

water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

WHMIS Classification: This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

15.3. US State regulations



WARNING: This product can expose you to methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

methanol (67-56)	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 – Developmental Toxicity	Yes
U.S. - California - Proposition 65 – Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 – Reproductive Toxicity - Male	No
No significant risk level (NSRL)	
Maximum allowable dose level (MADL)	47000 µg/day (inhalation). 23,000 µg/day (oral)

methanol (67-56-1)	
U.S. - Massachusetts - Right to Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

SECTION 16 OTHER INFORMATION

Revision date: 01/01/2020

Full text of H-statements:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H370	Causes damage to organs

NFPA health hazard: 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity: 0 - Material that in themselves are normally stable, even under fire conditions.

