

SUNEX[®]
T O O L S

**THE EPITOME OF
POWER & EFFICIENCY
IN A LIGHTWEIGHT DESIGN**

3/8" DRIVE

200% GREATER POWER
TO WEIGHT RATIO
VERSUS COMPARABLE PRODUCTS

261 $\frac{\text{FT-LB}}{\text{LB}}$
POWER TO
WEIGHT RATIO




- Crafted with a magnesium alloy clutch housing, this impact wrench offers reduced fatigue, superior durability, improved heat dissipation, and enhanced resistance to corrosion and impact damage
- The innovative 7 spring-loaded rotor blades ensure smoother operation and increased efficiency, leading to continuous high performance and a longer tool lifespan
- The durable, high-impact resistant handle, crafted from 40% glass-filled nylon, offers a reliable grip with superior impact and wear resistance

SX3802

3/8" DRIVE MAGNESIUM COMPOSITE IMPACT WRENCH

Magnesium Alloy front and rear housing at just 2.3 lbs., minimizes fatigue for longer use and provides durability, improved heat dissipation, and resistance to corrosion and impact, ensuring reliable, long-lasting performance



Variable speed throttle provides accurate control

The convenient one-hand switch regulator offers variable power settings, enabling multiple adjustments for different tasks while keeping your second hand free

The ergonomic handle design minimizes hand fatigue and improves user comfort ensuring a better user experience during prolonged use

The rotating air inlet enhances maneuverability, reduces hose twisting, and allows easier access to tight spaces, optimizing user comfort and efficiency

3/8" DRIVE

200% GREATER POWER TO WEIGHT RATIO VERSUS COMPARABLE PRODUCTS

261 $\frac{\text{FT-LB}}{\text{LB}}$
POWER TO WEIGHT RATIO

SPECIFICATIONS FOR SX3802

Square Drive	3/8"
Breakaway Torque	600 ft.-lbs.
Working Torque.....	400 ft.-lbs.
Free Speed	10,000 RPM
Average Air Consumption.....	4.5 CFM

Air Inlet.....	1/4" NPT
Minimum Hose Size	3/8" I.D.
Length	5.5"
Sound Level	100.8 dBA
Weight	2.3 lbs.