



SAFETY. SINCE 1898.™

# 88VX Series

## Airline Respirator

The Bullard 88VX Series airline respirators offer advancements in comfort and reliable respiratory protection for abrasive blasters and painters. The 88VX Respirator is NIOSH approved as a Type C and CE Continuous Flow Class Respirator (Approval No. TC-19C-0293).

### Advanced Protection

- Sewn-in neck cuff provides a physical barrier to airborne contaminants
- Double lining in the neck area enhances durability and protection

### Comfortable Fit

- Lightweight inner shell with an adjustable headband suspension
- Airflow is channeled directly to the user's breathing zone
- No fit testing required
- Optional cheek pads for increased stability

### Head Protection

- Helmet provides top impact and penetration protection
- Helmet and cape help protect the worker's entire head, face, and upper body from abrasive rebound, airborne contaminants and messy overspray

### Optimum Visibility

- Wide-angle faceshield lens
- Translucent yellow helmet prevents closed-in feeling among workers
- Optional tinted lenses provide protection from the sun

### Climate Control

- Optional climate control devices warm or cool incoming air to maximize comfort and improve productivity



[www.bullard.com](http://www.bullard.com)  
Assembled in the USA

©2023 Bullard. All rights reserved.  
8766 (1123)



SAFETY. SINCE 1898.™

# 88VX Parts List

## 88VXSYS

Includes a 88VX3235 respirator assembly, ADP20 Free -Air® pump, 50 foot (15 m) airsupply hose and Frigitron 2000 climate control device.

## Respirator Models

For use with breathing air compressors Includes EVX30 breathing tube assembly with 1/4" Industrial Interchange fitting and belt, inner and outer lenses and cape. Breathing air supply hose not included.

88VX3230	Respirator with 46VX nylon cape – 28" (71 cm) length
88VX3230H	Same as model 88VX3230 with 25' (8m) of starter hose
88VX1330	Same as model 88VX3230 with 13VX nylon cape – 38" (96cm) length

## For use with Bullard Free-Air® Pumps

Includes EVX35 breathing tube assembly with 1/2" Industrial Interchange fitting and belt, inner and outer lenses and cape. Breathing air supply hose not included.

88VX3235	Respirator with 46VX nylon cape – 28" (71 cm) length.
88VX3235H100	Same as model 88VX3235 with 100' (32 m) of starter hose

## Replacement Capes for 88VX Series Airline Respirators

46VX	Tan Nylon Cape – 28" (71 cm) length
13VX	Tan Nylon Cape – 38" (96 cm) length
21VX	"Golden Gate" Style, Tan Nylon Cape – 38" (96 cm) length
36VX	Hibernia Parka, Tan Nylon Parka with Long Sleeves – 38" (96 cm) length
36LVX	Hibernia Parka, Tan Nylon Parka with Long Sleeves – 38" (96 cm)length, XL

## Accessories for 88VX Series Airline Respirators

88VXTGP	Adjustable headband suspension with Plenum
88VXRTP	Adjustable Sure-Lock® ratchet headband suspension with Plenum
88VXAK	Oval Door/Gasket/Latch Kit
88CA	Carrying Strap
88VXBAIL	Replacement Bail for Latch Assembly (10/pkg)
88VXHP	Replacement Hinge Pins for Latch Assembly (10/pkg)
20NC	Elastic Chin Strap
88CK	Breathing Tube Connector Kit
BFW	Box Front Window Frame
77GLT	Box Front Glass Lens
77LG	Front Box Lens Gasket
G7713	Oval Window Gasket
GVXCP	Replaceable Cheek Pads, Pair
88VXOLG	Outer lenses .042", Pack of 25 - Tinted Green
88VXOLT	Outer lenses .030", Pack of 25 - Tinted Smoke

## Replacement Lenses for 88VX Series (Oval)

P771B	Inner plastic lens, .040" (1 mm) thick (25/pkg)
B771040	Outer plastic lens, .040" (1 mm) thick (200/pkg)
P771020	Outer plastic lens, .020" (0.5 mm) thick (50/pkg)
P771R	Outer plastic lens, .015" (0.4 mm) thick (50/pkg)
88VXLC	Clear Mylar lens cover, perforated edges (25/pkg)

## Replacement Breathing Tube Assemblies

88VXBT	Breathing tube only (fitting not included)
--------	--

## Optional Climate Control Breathing Tube Assemblies with quick-disconnect fitting and belt

AC1000	Cool tube with 1/4" Industrial Interchange, steel quick-disconnect fitting. Adjustable airflow. For use with breathing air compressors.
HC2400	Hot/Cold tube with 1/4" Industrial Interchange, steel quick disconnect fitting. Adjustable airflow. For use with breathing air compressors.
Frigitron 2000	Cool tube with 1/2" Industrial Interchange, steel quick-disconnect fitting. Adjustable airflow. For use with Bullard ADP20 or ICE piston pumps.
DC5040	Dual-Cool with 1/4" Industrial Interchange for use with breathing air compressors. Order Dual-Cool vests separately.
DC70ML	Dual-Cool vest. Size M/L
DC70XLXXL	Dual-Cool vest. Size XL/XXL

## Air Supply Hoses and Fittings

V10 Series Starter and Extension Hose Kits (For use with Breathing Air Compressors) Includes 3/8" (10 mm) I.D. rubber hose, V11 hose-to-hose adapter fitting and V13 adapter fitting - 3/8" (10 mm) hose-to-3/8" (10 mm) pipe.

4696	25' (8 m) Starter hose kit with 1/4" Industrial Interchange, steel quick-disconnect fittings
5454	25' (8 m) Extension hose kit
5457	50' (15 m) Extension hose kit
5458	100' (31 m) Extension hose kit

V20 Series Starter Hoses (For use with Free-Air Pumps) Includes 1/2" (13 mm) I.D. rubber hose with 1/2" Industrial Interchange male/female quick-disconnect coupler.

V2050ST 50' (15 m)
V20100ST 100' (31 m)

**Bullard Center**  
2421 Fortune Drive  
Lexington, KY 40509 • USA  
877-BULLARD (285-5273)  
Tel: +1-859-234-6616  
Fax: +1-859-246-0243

**Americas Operations**  
1898 Safety Way  
Cynthiana, KY 41031 • USA  
877-BULLARD (285-5273)  
Tel: +1-859-234-6616  
Fax: +1-859-234-8987

**Bullard GmbH**  
Dieselstrasse 8a  
53424 Remagen • Germany  
Tel: +49-2642 999980  
Fax: +49-2642 9999829

**Bullard Asia-Pacific Pte. Ltd.**  
51 Changi Business Park  
Central 2  
#03-04 The Signature  
Singapore 486066  
Tel: +65 6745 0556

[www.bullard.com](http://www.bullard.com)

©2023 Bullard. All rights reserved.  
Free-Air is a registered trademark of Bullard.  
Mylar is a registered trademark of Dupont Teijin Films.  
8766 (1123)