



**GUARDIAN**[®]

VELOCITY-EDGE CABLE

Self-Retracting Lifeline

The Velocity-Edge Class 2 SRL is both durable and lightweight to meet the demands of workers who require a straightforward, no-nonsense cable SRL. The Velocity-Edge SRL features a useful carrying handle that allows for easier installation and reduces fatigue while transporting the device on site. The Velocity-Edge SRL can be used for numerous applications across a jobsite where the connecting device has potential to impact the edge of a hazard in the event of a fall.

Class
2
Anchor above
or below dorsal
D-ring

**HEIGHT SAFETY.
SIMPLIFIED.**

guardianfall.com



VELOCITY-EDGE CABLE

Self-Retracting Lifeline



Class

2

Anchor above
or below dorsal
D-ring



4200110



Se puede utilizar en aplicaciones borde expuesto

Key features & benefits

Swivel top connection point

Swivels 360-degrees to ensure the device remains in the best orientation during use and also helps prevent lifeline snagging or tangling. Double-locking carabiner included.

Thermoplastic housing

Heavy-duty and durable for long lasting use in the toughest applications

Integrated handle

Allows for user comfort when carrying and installing the SRL

QR code enabled labels

Easy access to product information

Steel cable lifeline

Resists cuts and abrasions

Guardian shock pack cover

Helps increase product longevity and protects safety labeling

Integrated fall clearance charts

Fall Clearance charts integrated into shock pack cover for easy access to clearance charts anytime, anywhere

Swivel carabiner

Swivels 360-degrees to ensure the device remains in the best orientation

Specifications

User weight range (including clothing, tools, & equipment)

ANSI (LE use) | 130-310 lb (59-141 kg)

OSHA (Non-LE use) | 100-420 lb (45-191 kg)

Max. Arrest Force | 1,800 lb (8 kN)

Avg. Arrest Force | 1,350 lb (6 kN)

Materials | Galvanized steel, aluminum, stainless steel, polyolefin, polyester

Non-LE use (Anchor at or above dorsal D-ring)

Max. Arresting Distance | 3 ft 6 in (1,1 m)

Max. Allowable Free Fall | Not Permitted

Min. Fall Clearance | 7 ft (2,1 m)

LE Use (Anchor below dorsal D-ring)

Min. Setback Distance from Edge | 0 ft (0 m)

Max. Arresting Distance | 9 ft 6 in (2,8 m)

Max. Allowable Free Fall | 5 ft (1,5 m)

Min. Fall Clearance | 18 ft (5,5 m)

Declaration of conformity

This product has been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:
OSHA 1910.140 & 1926.502 | ANSI Z359.14

For more information:

+1 (800) 466 6385


customer.service@guardianfall.com



Tested in the
United States

VELOCITY-EDGE CABLE

Self-Retracting Lifeline



Part numbers	Description	Hook type	Length	User Weight Range
4200108	Velocity-Edge Cable Class 2 SRL	Aluminum Carabiner	16 ft (4,8 m)	See Specifications
4200109	Velocity-Edge Cable Class 2 SRL	Aluminum Carabiner	20 ft (6,1 m)	See Specifications
4200110	Velocity-Edge Cable Class 2 SRL	Aluminum Carabiner	30 ft (9,1 m)	See Specifications
4200111	Velocity-Edge Cable Class 2 SRL	Aluminum Carabiner	50 ft (15,2 m)	See Specifications

Declaration of conformity

This product has been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:
OSHA 1910.140 & 1926.502 | ANSI Z359.14

For more information:

+1 (800) 466 6385

customer.service@guardianfall.com



Tested in the
United States