

Issue Date 09-Apr-2015

Revision Date 08-Sep-2025

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier.

Product Name Gordon's® MALATHION 50% Spray

Other means of identification

Product Code PBI FP 893-6

EPA Pesticide Registration Number 33955-394

Recommended use of the chemical and restrictions on use

Recommended Use Insecticide

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address

PBI-Gordon Corporation
P.O. Box 860350
Shawnee, KS 66286

Company Name

PBI-Gordon Corporation
P.O. Box 860350
Shawnee, KS 66286

Manufacturer

PBI-Gordon Corporation
P.O. Box 860350
Shawnee, KS 66286

Emergency telephone number

24 Hour Emergency Phone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute Oral Toxicity	Category 4
Acute dermal toxicity	Category 4
Acute Inhalation Toxicity - Gases	Category 3
Skin Sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Aspiration hazard	Category 1
Acute Aquatic Toxicity	Category 1
Chronic Aquatic Toxicity	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Signal word

Danger

Hazard statements

- Harmful if swallowed or in contact with skin
- Toxic if inhaled
- May cause an allergic skin reaction
- May cause genetic defects
- May cause cancer
- Very toxic to aquatic life with long lasting effects
- May be fatal if swallowed and enters airways
- Flammable liquid and vapor

					
Appearance	Liquid	Physical state	Liquid	Odor	Mercaptan

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Call a POISON CENTER or doctor if you feel unwell
If skin irritation or rash occurs: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
Wash contaminated clothing before reuse
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor
IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting
Rinse mouth
In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Have the product label with you when calling a poison control center or doctor or going in for treatment. You may also contact 1-877-800-5556 for emergency medical treatment advice.

Other information

Not applicable.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Substance**

Not applicable.

Mixture

Chemical name	CAS-No	Weight-%
Malathion	121-75-5	50
Trade Secret	Trade secret	30-60*

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures**

General advice	IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. If symptoms persist, call a physician.
Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Remove all sources of ignition. See section 8 for more information. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms	Itching Rashes Hives Difficulty in breathing Coughing and/ or wheezing Dizziness
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
---------------------------	--

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u>	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
--	--

<u>Unsuitable extinguishing media</u>	CAUTION: Use of water spray when fighting fire may be inefficient.
--	--

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal precautions**

See section 8 for more information. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid contact with skin, eyes or clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Use personal protective equipment as required.

Environmental precautions**Environmental precautions**

Prevent further leakage or spillage if safe to do so Prevent product from entering drains Do not flush into surface water or sanitary sewer system See Section 12 for additional ecological information Avoid release to the environment Collect spillage Dispose of contents/container to an approved waste disposal plant

Other information

Ventilate the area. For further specification, refer to section 8 of the SDS.

Methods and material for containment and cleaning up**Methods for containment**

Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Malathion 121-75-5	TWA: 1 mg/m ³ inhalable fraction and vapor S*	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust (vacated) S* S* total dust	IDLH: 250 mg/m ³ TWA: 10 mg/m ³

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Hand protection

Impervious gloves. Wear suitable gloves.

Skin and body protection

Chemical resistant apron. Antistatic boots. Long sleeved clothing. Wear suitable protective clothing.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General hygiene considerations

Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Liquid
Appearance	Liquid
Color	Light yellow
Odor	Mercaptan
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	
Melting point/freezing point		None known
Boiling point / boiling range	149 °C / 300 °F	
Flash point	41 °C / 106 °F	
Evaporation rate	< 1	
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Vapor pressure	<16 mm Hg@20°C	
Vapor density	>1	
Specific Gravity	1.051	
Water solubility	Emulsifiable	
Solubility in other solvents	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known

Other Information

Liquid Density	8.7 pounds/gallon
Bulk density	No information available

10. STABILITY AND REACTIVITY**Reactivity**

No information available.

Stability

No information available

Possibility of hazardous reactions

None under normal processing.

Hazardous polymerization

Will not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

May emit toxic fumes under fire conditions. Hydrogen sulfide. Methyl Mercaptan. Dimethyl Sulfide. Oxides of sulfur. Carbon oxides. Phosphorus oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Repeated exposure may cause skin dryness or cracking. May be absorbed through the skin in harmful amounts. Harmful in contact with skin. (based on components).
Ingestion	Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Specific test data for the substance or mixture is not available. (based on components).

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Malathion 121-75-5	= 1390 mg/kg (Rat)	= 4100 mg/kg (Rabbit)	= 43790 µg/m ³ (Rat) 4 h
Trade Secret	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Acute toxicity

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-gas) 726 mg/L

Unknown Toxicity

2 % of the mixture consists of ingredient(s) of unknown toxicity

2 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

2 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

LD50 Oral	> 2000 mg/kg (rat)
LD50 Dermal	> 2000 mg/kg (rabbit)
LC50 Inhalation (DUST)	> 5.10 mg/L

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	May cause sensitization by skin contact.

Germ cell mutagenicity Classification based on data available for ingredients. Contains a known or suspected mutagen.

Carcinogenicity Classification based on data available for ingredients.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Malathion 121-75-5	-	Group 2A	-	X

Legend

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Target Organ Effects Liver, Respiratory system, Eyes, Skin, Central nervous system, blood, Gastrointestinal tract (GI), Central Vascular System (CVS).

Aspiration hazard May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Marine pollutant This product contains a chemical which is listed as a marine pollutant according to DOT.

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Malathion 121-75-5	4.06: 72 h Pseudokirchneriella subcapitata mg/L EC50	0.0022 - 0.0074: 96 h Oncorhynchus mykiss mg/L LC50 static 0.010 - 0.088: 96 h Lepomis macrochirus mg/L LC50 static 0.094 - 0.146: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 0.24 - 1.24: 96 h Cyprinus carpio mg/L LC50 static 12.3 - 16.1: 96 h Pimephales promelas mg/L LC50 flow-through 6.45 - 11.5: 96 h Pimephales promelas mg/L LC50 static 0.002: 96 h Cyprinus carpio mg/L LC50 0.028: 96 h Oncorhynchus mykiss mg/L LC50 0.085: 96 h Cyprinus carpio mg/L LC50 semi-static 0.089: 96 h Lepomis macrochirus mg/L LC50 0.34: 96 h Lepomis macrochirus mg/L LC50 flow-through 1.2: 96 h Poecilia reticulata mg/L LC50 10.1: 96 h Pimephales promelas mg/L LC50	-	0.00014 - 0.014: 48 h Daphnia magna mg/L EC50

		3.1: 96 h <i>Poecilia reticulata</i> mg/L LC50 static 9.7: 96 h <i>Oryzias latipes</i> mg/L LC50 static		
Trade Secret	-	9.22: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50	-	6.14: 48 h <i>Daphnia magna</i> mg/L EC50

Persistence and degradability No information available.

Bioaccumulation No information available.

Component Information

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number D001.

14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1993
 Proper shipping name FLAMMABLE LIQUID, N.O.S.
 Hazard class 3
 Packing group III
 Reportable Quantity (RQ) Malathion: RQ (gallons)= 22 gallons
 Special Provisions B1, B52, IB3, T4, TP1, TP29
 Marine pollutant This product contains a chemical which is listed as a marine pollutant according to DOT.
 Description UN1993, FLAMMABLE LIQUIDS, N.O.S., 3, III Limited quantity

TDG

UN/ID no. UN1993
 Proper shipping name FLAMMABLE LIQUID, N.O.S.
 Hazard class 3
 Packing group III
 Marine pollutant This product contains a chemical which is listed as a marine pollutant according to TDG.
 Description UN1993, FLAMMABLE LIQUIDS, N.O.S., 3, III Limited quantity

MEX

UN/ID no. UN1993
 Proper shipping name FLAMMABLE LIQUID, N.O.S.
 Hazard class 3
 Packing group III
 Description UN1993, FLAMMABLE LIQUIDS, N.O.S., 3, III Limited quantity

ICAO (air)

Limited quantity applies with an inner packaging less than 5 L or gross package weight less than 30 kg.
 UN/ID no. UN1993
 Proper shipping name FLAMMABLE LIQUID, N.O.S.
 Hazard class 3
 Packing group III

Special Provisions Description	A3 UN1993, FLAMMABLE LIQUID, N.O.S. (1,2,4 Trimethylbenzene, Cumene), 3, III
---------------------------------------	---

IATA	Limited quantity applies when the inner packaging weight is less than 5kg and the gross package weight is less than 30kg.
UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
Transport hazard class(es)	3
Packing group	III
Special Provisions Description	A3 UN1993, FLAMMABLE LIQUID, N.O.S. (1,2,4 Trimethylbenzene, Cumene), 3, III

IMDG	Limited quantity applies when the inner packaging weight is less than 5kg and the gross package weight is less than 30kg.
UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S.
Transport hazard class(es)	3
Packing group	III
EmS-No.	F-E, S-E
Special Provisions Description	223, 274, 955 UN1993, FLAMMABLE LIQUID, N.O.S. (1,2,4 TRIMETHYLBENZENE, CUMENE), 3, III, (41°C C.C.), MARINE POLLUTANT

15. REGULATORY INFORMATION

U.S. EPA Label Information

EPA Pesticide Registration Number 33955-394

Federal Insecticide, Fungicide, Rodenticide Act Regulations

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

International Inventories

TSCA	Listed
DSL/NDSL	Listed
EINECS/ELINCS	Listed
ENCS	Not Listed
IECSC	Listed
KECL	Listed
PICCS	Listed
AICS	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
---------------	-------------------------------

Malathion - 121-75-5	0.1
----------------------	-----

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Malathion 121-75-5	100 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs
Malathion 121-75-5	100 lb	-

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Malathion - 121-75-5	Carcinogen
Trade Secret -	Carcinogen
Trade Secret -	Carcinogen Developmental Female Reproductive Male Reproductive
Trade Secret -	Carcinogen

U.S. State Right-to-Know Regulations**US State Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Malathion 121-75-5	X	X	X
Trade Secret	X	X	X
Trade Secret	X	-	X

16. OTHER INFORMATION**NFPA**

Health hazards 3

Flammability 2

Instability 0

Physical and Chemical
Properties -**HMIS**

Health hazards 3 *

Flammability 2

Physical hazards 0

Personal protection X

Chronic Hazard Star Legend

* = Chronic Health Hazard

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of PBI-Gordon Corporation's knowledge, information and belief at the date of this publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process, unless specified in the text. PBI-GORDON CORPORATION MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of this product, some of which are

uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. Each user is also responsible for evaluating the conditions of use and designing the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. PBI-Gordon Corporation assumes no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

End of Safety Data Sheet