

Safety Data Sheet

Regulation: In accordance with Regulation (EU) 2015/830 (REACH), Annex II, and OSHA 29 CFR 1910.1200

1. PRODUCT AND COMPANY IDENTIFICATION

Important Note: As a solid, manufactured article, exposure to hazardous ingredients is not expected with normal use. This battery is an article pursuant to 29 CFR 1910.1200 and, as such, is not subject to the OSHA Hazard Communication Standard requirement. The information contained in this Safety Data Sheet contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Product Name: 21" Flagship Single-stage Push Snow Blower Kit (2*6.0Ah, 560W dual port charger)

Model Number: SNT2134

Substance name: Battery Pack (Packed with equipment)

Synonyms: Lithium-ion Battery, Lithium-ion Battery Pack, Li-Ion Battery, Li-Ion Battery Pack

Manufacturer: Nanjing Chervon Industry Co., Ltd.

Address: 529 South Jiang Jun Rd. Jiangning Economic & Technical Development Zone

Nanjing, Jiangsu 211106 P. R. China

Company/undertaking Identification: 1-352-323-3500 international (Account number: 109087)

Further Information:

Battery-System: Lithium-ion (Li-ion)

Battery Model: BA3360T

Number of battery packs packed with the product: 2

Nominal Voltage: 56 V

Rated Capacity: 6.0 Ah

Wh Rating: 336 Wh

2. HAZARDS IDENTIFICATION

GHS Classification

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Label elements

Symbols/Pictograms	None
Signal word	None
Hazard Statements	Not classified.
Precautionary Statements	
Prevention	None.
Response	None.
Storage	None.

Disposal

None.

Hazards not otherwise classified (HNOC)

No information available

Unknown acute toxicity

No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

The battery pack contains different quantity battery cells in it depending on the battery pack capacity.

Battery Pack Model Number	Quantity of the Battery Cells
BA3360T	42
BA3360T	42

Chemical nature

Article

Chemical Name	CAS No	Weight-%
Cobalt lithium manganese nickel oxide	182442-95-1	30-32
Iron	7439-89-6	22-23
Copper	7440-50-8	15-16
Graphite	7782-42-5	14-15
Aluminum	7429-90-5	7-8
Polypropylene	9003-07-0	2-3
Phosphate(1-), hexafluoro-, lithium	21324-40-3	2-3

4. FIRST-AID MEASURES

Description of first aid measures

General advice	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Inhalation	Not an expected route of exposure, IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin contact	Wash hands thoroughly after handling.
Eye contact	Not an expected route of exposure. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Ingestion	Not an expected route of exposure. If swallowed, call a poison control center or physician immediately.

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

No information available.

Special hazards arising from the chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors

Carbon oxides(CO_x), metal oxides

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Evacuate personnel to safe areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Use personal protection recommended in Section 8. Avoid contact with skin, eyes or clothing. Do not touch or walk through spilled material. Avoid breathing vapors or mists.

Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so.

Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precaution for safe handling

Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation, especially in confined areas. Avoid generation of dust. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Use personal protection recommended in Section 8. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

Condition for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition. Keep locked up and of reach of children. Keep away from food, drink and animal feeding stuffs. Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	Denmark	European Union
Cobalt lithium manganese nickel oxide (CAS #:182442-95-1)	TWA: 0.02mg/m ³ Co TWA: 0.02mg/m ³ Mn	-	IDLH:500 mg/m ³ Mn IDLH:10 mg/m ³ Ni TWA:1 mg/m ³ Mn	TWA:0.01 mg/m ³ TWA:0.2 mg/m ³	-

	TWA: 0.1mg/m ³ Mn		TWA:0.015 mg/m ³ except Nickel carbonyl Ni STEL:3 mg/m ³ Mn		
Copper (CAS#:7440-50-8)	TWA:0.2mg/m ³ fume TWA:1mg/m ³ Cu dust and mist	--	IDHL:100 mg/m ³ dust, fume and mist IDHL:100 mg/m ³ Cu dust and mist TWA:1 mg/m ³ dust and mist TWA:0.1 mg/m ³ fume TWA:1 mg/m ³ Cu dust and mist	TWA:1.0 mg/m ³ TWA:0.1 mg/m ³	-
Graphite (CAS#:7782-42-5)	TWA:2mg/m ³ respirable fraction all forms except graphite fibers	-	IDHL:1250 mg/m ³ TWA:2.5 mg/m ³ natural respirable dust	TWA:2.5 mg/m ³	-
Aluminum (CAS#:7429-90-5)	TWA:1 mg/m ³ respirable fraction	TWA:15mg/m ³ total dust TWA:5mg/m ³ respirable fraction (vacated) TWA:15 mg/m ³ total dust (vacated) TWA:5 mg/m ³ respirable fraction (vacated) TWA:5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 5 mg/m ³ Al	TWA: 5 mg/m ³ TWA: 2 mg/m ³	-
Phosphate(1-), hexafluoro-,lithium (CAS#:21324-40-3)	TWA:2.5 mg/m ³ F	-	--	TWA:2.5 mg/m ³	-

Chemical Name	Latvia	France	Finland	Germany	Italy
Cobalt lithium manganese nickel oxide (CAS #: 182442-95-1)	TWA: 0.05 mg/m ³	-	TWA: 0.05 mg/m ³ TWA: 0.01 mg/m ³ TWA: 0.02 mg/m ³ TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³ TWA: 0.02 mg/m ³ Ceiling/Peak: 1.6mg/m ³ Ceiling/Peak: 0.16mg/m ³ Ceiling/Peak: 0.2mg/m ³ Skin TWA: 0.5mg/m ³	-
Copper (CAS#:7440-50-8)	TWA: 0.5 mg/m ³ STEL: 1 mg/m ³	TWA: 0.2mg/m ³ TWA: 1 mg/m ³	TWA: 1 mg/m ³ TWA: 0.1 mg/m ³	TWA: 0.01 mg/m ³ Ceiling/Peak: 0.02	-

		STEL: 2 mg/m ³		mg/m ³ Ceiling/Peak: 0.2mg/m ³	
Graphite (CAS#:7782-42-5)	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 1.5 mg/m ³ TWA: 4 mg/m ³	-
Aluminum (CAS#:7429-90-5)	TWA: 2 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 1.5 mg/m ³	TWA: 4 mg/m ³ TWA: 1.5 mg/m ³	-
Polypropylene (CAS#:9003-07-0)	TWA: 5 mg/m ³	-	-	-	-
Phosphate(1-), hexafluoro-,lithium (CAS#:21324-40-3)		-	-	TWA: 1 mg/m ³ Skin	-

Chemical Name	Poland	Portugal	Spain	Switzerland	Netherlands
Copper (CAS#:7440-50-8)	-	-	-	-	TWA: 0.1 mg/m ³
Aluminum (CAS#:7429-90-5)	TWA: 2.5 mg/m ³ TWA: 1.2 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 3 mg/m ³	-

Chemical Name	Norway	United Kingdom	Australia	Austria	Belgium
Cobalt lithium manganese nickel oxide (CAS #: 182442-95-1)	TWA: 0.05 mg/m ³ TWA: 0.02 mg/m ³ TWA: 1 mg/m ³ TWA: 0.1 mg/m ³ STEL: 0.05 mg/m ³ STEL: 0.02 mg/m ³ STEL: 1 ppm STEL: 0.1 mg/m ³	-	1 mg/m ³	Skin STEL: 2 mg/m ³ TWA: 0.5 mg/m ³	-
Copper (CAS#:7440-50-8)	TWA: 0.1 mg/m ³ TWA: 1 mg/m ³ STEL: 0.1 mg/m ³ STEL: 1 mg/m ³	-	1 mg/m ³ 0.2 mg/m ³	STEL: 4 mg/m ³ STEL: 0.4 mg/m ³ TWA: 1 mg/m ³ TWA: 0.1 mg/m ³	-
Graphite (CAS#:7782-42-5)	TWA: 5 mg/m ³ TWA: 2 mg/m ³ TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 5 mg/m ³ STEL: 2 mg/m ³ STEL: 10 mg/m ³ STEL: 4 mg/m ³	-	3 mg/m ³	STEL: 10 mg/m ³ TWA: 5 mg/m ³	-
Aluminum (CAS#:7429-90-5)	TWA: 5 mg/m ³ STEL: 5 mg/m ³	STEL: 30 mg/m ³ STEL: 12 mg/m ³ TWA: 10 mg/m ³ TWA: 4 mg/m ³	10 mg/m ³ 5 mg/m ³	STEL: 20 mg/m ³ TWA: 10 mg/m ³	-
Phosphate(1-),	-	-	2.5 mg/m ³	-	-

hexafluoro-,lithium (CAS#:21324-40-3)					
--	--	--	--	--	--

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Removed all sources of ignition.

Individual protection measures, such as personal protective equipment

Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentration. Respiratory protection must be provided in accordance with current local regulations.
Hand protection	Wear protective gloves.
Eye/face protection	No special technical protective measures are necessary.
Skin and body protection	Suitable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Solid
Color	No information available
Odor	No information available
Odor Threshold	Not determined
pH	Not determined
Melting point/freezing point	Not determined
Boiling point/boiling range	Not determined
Flash point	Not applicable
Evaporation rate	Not determined
Flammability (solid, gas)	Not flammable
Flammability Limit in Air	Not applicable
Vapor Pressure	Not determined
Vapor density	Not applicable
Density	Not determined
Relative density	Not determined
Bulk density	Not determined
Specific gravity	Not determined
Water solubility	Not determined
Partition coefficient (LogPow)	Not determined
Autoignition temperature	Not applicable
Decomposition temperature	Not determined
Kinematic viscosity	Not determined
Dynamic viscosity	Not determined
Explosive properties	Not an explosive
Oxidizing properties	Not determined

Other information

No information available

10. STABILITY AND REACTIVITY

Reactivity

Stable under recommended storage and handling conditions (see SECTION 7, handling and storage).

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing

Conditions to avoid

Strong heating. Incompatible materials.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

Hazardous Decomposition Products

Carbon oxides (CO_x), metal oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Not an expected route of exposure
Eye contact	Dust contact with the eyes can lead to mechanical irritation
Skin contact	No known effect based on information supplied
Ingestion	Not an expected route of exposure

Information on toxicological effects

Acute toxicity

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Iron (CAS#: 7439-89-6)	98.6 g/kg bw(rat)	-	-
Copper (CAS#:7440-50-8)	> 2500 mg/kg bw(rat)	> 2000 mg/kg bw(rat)	=1.03 mg/L/4h (rat)
Graphite (CAS#:7782-42-5)	> 2000 mg/kg (rat)	-	> 2000 mg/m ³ /4h(rat)
Aluminum (CAS#:7429-90-5)	LD50> 15900 mg/kg bw(rat)	-	LC50>0.888 mg/L/4h(rat)
Polypropylene (CAS#:9003-07-0)	> 5g/kg	-	-

Skin corrosion/irritation

Non-irritating to the skin

Serious eye damage/eye irritation

No eye irritation

Sensitization

No information available

Germ cell mutagenicity

No information available

Carcinogenicity

Chemical name	ACGIH	IARC	NTP	OSHA
Cobalt lithium manganese nickel oxide (CAS#: 182442-95-1)	A3	-	Known	-
Polypropylene (CAS#:9003-07-0)	-	Group 3	-	-

Reproductive toxicity

No information available

STOT- single exposure

No information available

STOT- repeated exposure

No information available

Aspiration hazard

No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/aquatic plants EC50	Fish LC50	Crustacea EC50
Iron (CAS#: 7439-89-6)	-	13.6: 96h Morone saxatilis mg/L LC50 static	> 100mg/l/48h (Daphnia magna)
Copper (CAS#:7440-50-8)	0.031-0.054mg/L/96h Pseudokirchneriella subcapitata static 0.0426-0.0535mg/L/72h Pseudokirchneriella subcapitata static	1.25: 96h Lepomis macrochirus mg/L LC50 static 0.3: 96h Cyprinus carpio mg/L LC50 semi-static 0.8: 96h Cyprinus carpio mg/L LC50 static 0.112: 96h Poecilia reticulata mg/L LC50 flow-through 0.0068-0.0156: 96h Pimephales	-

		promelas mg/L LC50 0.3:96h Pimephales promelas mg/L LC50 static 0.2:96h Pimephales promelas mg/L LC50 flow- through 0.052: 96h Oncorhynchus mykiss mg/L LC50 flow- through	
Graphite (CAS#:7782-42-5)	>100mg/L/72h (Pseudokirchneriella subcapitata)	>100mg/L/96h (Danio rerio)	>100mg/L/48h (Daphnia magna)
Aluminum (CAS#:7429-90-5)	-	>50mg/L/96h	-

Persistence and degradability

No information available

Bioaccumulative potential

No information available

Mobility in soil

No information available

Other adverse effects

No information available

13. DISPOSAL CONSIDERATION

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations

Contaminated packaging

Dispose of in accordance with federal, state and local regulations

Chemical Name	California Hazardous Waste Status
Cobalt lithium manganese nickel 182442-95-1	Toxic
Copper 7440-50-8	Toxic
Aluminum 7429-90-5	Ignitable powder

14. TRANSPORT INFORMATION

UN Number: UN 3481

Proper Shipping Name: Lithium ion batteries packed with equipment

Hazard Class: 9

ICAO/IATA (air transportation):

The product shall meet the General Requirements and Packaging Instruction 966 I.

IMO (sea transportation):

The product shall meet the General Requirements and Packing instruction of P903, P908, P909, P910, LP903 & LP904.

U.S. DOT (ground transportation):

The product shall meet the requirement of US Hazardous Materials Regulations 49 CFR (Code of Federal Regulations) Sections 173.185 in USA.

Canada TDG (ground transportation):

The product shall meet the requirement of Transportation of Dangerous Goods Regulations in Canada.

European Agreements ADR/RID/AND (ground transportation):

The product shall meet the General Requirements and Packing instruction of P903, P908, P909, P910, LP903 & LP904.

Australian Dangerous Goods ADG (ground transportation):

The product shall meet the General Requirements and Packing instruction of P903, P908, P909, P910, LP903 & LP904.

15. REGULATORY INFORMATION

International Inventories

Component	AICS	DSL/NDSL	EINECS/ ELINCS	ENCS	IECSC	KECL	PICCS	TSCA
Cobalt lithium manganese nickel 182442-95-1 (30-32)	-	-	-	-	X	-	-	X
Iron 7439-89-6 (22-23)	X	X	X	Exempt	X	X	X	X
Copper 7440-50-8 (15-16)	X	X	X	Exempt	X	X	X	X
Graphite 7782-42-5 (14-15)	X	X	X	Exempt	X	X	X	X
Aluminum 7429-90-5 (7-8)	X	X	X	Exempt	X	X	X	X
Polypropylene 9003-07-0 (2-3)	X	X	-	X	X	X	X	X
Phosphate(1-), hexafluoro-,lithium 21324-40-3 (2-3)	X	X	X	X	X	X	X	X

"-" Not listed

"X" Listed

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 196 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313-Threshold Values %
Aluminum-7429-90-5	1.0

SARA 311/312 Hazard Categories

Not applicable

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA-Reportable Quantities	CWA-Toxic Pollutants	CWA-Priority Pollutants	CWA-Hazardous Substances
Cobalt lithium manganese nickel 182442-95-1	-	X	-	-
Copper 7440-50-8	-	X	X	-

CERCLA

Not applicable

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Cobalt lithium manganese nickel 182442-95-1	Carcinogen

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Cobalt lithium manganese nickel 182442-95-1	X	-	-
Copper 7440-50-8	X	X	
Graphite 7782-42-5	X	X	
Aluminum 7429-90-5	X	X	X
Phosphate(1-), hexafluoro-,lithium 21324-40-3	X	-	-

16. OTHER INFORMATION

Revision Note

Issue Date

12-Jan-2016

Revision date
Revision Note

27-Feb-2018
Update transport information

Key or legend to abbreviations and acronyms used in the safety data sheet

TWA – TWA (time-weighted average)

STEL – STEL (Short Term Exposure Limit)

Ceiling – Maximum limit value

TSCA – United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL – Canadian States Toxic Substances List/Non-Domestic Substances List

EINECS/ELINCS – European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS – Japan Existing and New Chemical Substances

IECSC - China Existing and New Chemical Substances

KECL – Korean Existing and Evaluated Chemical Substances

PICCS – Philippines Inventory of Chemical and Chemical Substances

AICS – Australian Inventory of Chemical Substances

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the test.