

GP6700E

GP SERIES Portable Generator

1 of 2

Model 8062-0 UPC: 696471104516
(49-State)

Features

- **Dual Fuel** – Runs on gasoline or Liquid Propane fuel.
- **11-Hour Runtime** when running on gasoline and 6-Hour Runtime on 20lb LP tank when 50% of power is being used.
- **Easy-to-Use Electric Start** – Rocker switch provides reliable and hassle-free start ups (Battery included).
- **Reliable OHV Engine** – 340cc with splash lubrication provides a long engine life.
- **Handle & Wheel Kit** – Ergonomic handle and never-flat wheel kit included for portability.
- **1 1/4" steel-tube cradle** for added durability and strength.
- **3ft Adapter Cord Included** – 3ft 30A cable adapter included to make getting powered up even easier.
- **Covered outlets** provide added protection from the environment and rugged working conditions.
- **Low-oil level shutdown** automatically safeguards engine from damage.
- **COsense® Technology** – STOPS, ALERTS, SAVES. Powerful protection against hazardous carbon monoxide.
- **HomeLink™ Manual Transfer Switch compatible** designed to work with HomeLink™ manual transfer switches for safe home backup power.




Running Watts 6700 (Gas) / 6000 (LP)
Starting Watts 8250 (Gas) / 7425 (LP)



30A Adapter Cord

Control Panel



GP6700E DF

Specifications

Product Series	GP6700E DF
Model Number	8062-0
Configuration	49-State
AC Rated Output Running Watts	6700 (Gas) / 6000 (LP)
AC Maximum Output Starting Watts	8250 (Gas) / 7425 (LP)
Rated AC Voltage	120/240 VAC
Rated AC Frequency	60 Hz
Rated 120/240 VAC Amperage	55.8/27.9 (Gas) / 50/25 (LP)
Engine Displacement	340cc
Engine Type	OHV
Engine RPM	3600
Recommended Oil	10W-30 / SAE 30
Oil Capacity qt (L)	1.06 (1.0)
Lubrication Method	Splash
Automatic Voltage Regulation (AVR)	Yes
Choke Location	On Engine
Fuel Shut Off	On Fuel Tank
Starting Method	Electric Start / Recoil Pull Start

Battery Included	Yes
Battery Type	Lead Acid (12V DC, 9Ah)
Battery Part No.	A0006353770
Battery Dimensions	5.94" x 2.56" x 3.70"
Low Oil Shutdown	Yes
Neutral Bonded to Ground	Yes
Start Switch Type	Off/Run/Start
Start Switch Location	On Control Panel
Fuel Gauge	Yes
Fuel Tank Capacity gal (L)	7.5 (28.4)
Run Time at 25% (Hours)	11 (Gas) / 6 (LP)
Run Time at 50% (Hours)	15
Handle Style	Dual Grip, Single Folding with Lock Pin
Wheel Type	9.5" Never Flat
Warranty- Residential	3 Year Limited
Warranty- Commercial	2 Year Limited
Included	Engine oil, handle & wheel kit, battery, owner's manual, LP hose with primary regulator to connect to 20lb LP tank and 30 Amp adapter cord

Dimensions and Weights

Length in (mm)	27.5 (698)
Width in (mm)	27 (684)
Height in (mm)	26.5 (674)
Extended Length in (mm)	45 (1143)
Carton Length in (mm)	28.5 (725)
Carton Width in (mm)	21.7 (550)
Carton Height in (mm)	28 (710)
Unit Weight lbs (kg)	180 (81.5)
Shipping Weight lbs (kg)	192 (86.9)

